

IN THE CLAIMS

Please amend the claims as follows:

1. (original) A circuit arrangement (1, 41, 51, 61) for operating one or more low-pressure gas discharge lamps (24), comprising a current converter (14) and a driving device (13) for the current converter (14), characterized in that a second current converter (15) generates a voltage (32, 33) phase-shifted by 180°.
2. (original) A circuit arrangement (1) for converting DC current into AC current and for feeding one or more low-pressure gas discharge lamps (24) which utilizes a full-bridge switching circuit (2) with power switches (16, 17, 18, 19) as current converters (14, 15) and two resonant circuits (4, 5, 20, 21, 22, 23) per lamp (24), each of the resonant circuits (4, 5, 20, 21, 22, 23) having a series-connected coil (20, 21), one series-connected capacitor (4, 5) and one parallel-connected capacitor (22, 23).
3. (original) A circuit arrangement (41) for converting DC current into AC current and for feeding one or more low-pressure gas discharge lamps (24), which utilizes a full-bridge switching circuit (2) including power switches (16, 17, 18, 19) as current converters (14, 15), two series-connected capacitors (42, 43) and

two resonant circuits (20, 21, 22, 23) per lamp (24), each of the resonant circuits (20, 21, 22 or 23) having one series-connected coil (20, 21) and one parallel-connected capacitor (22, 23).

4. (original) A circuit arrangement (51) for converting DC current into AC current and for feeding one or more low-pressure gas discharge lamps (24) which utilizes a full-bridge switching circuit (2) with power switches (16, 17, 18, 19) as current converters (14, 15) and one resonant circuit (54, 55, 56) per lamp (24), which resonant circuit includes one series-connected coil (55), one series-connected capacitor (54) and one parallel-connected capacitor (56).

5. (original) A circuit arrangement (61) for converting DC current into AC current and for feeding one or more low-pressure gas discharge lamps (24), which utilizes a full-bridge switching circuit (2) with power switches (16, 17, 18, 19) as current converters (14, 15), two series-connected capacitors (62, 63) and one resonant circuit (55, 56) per lamp (24), which resonant circuit includes a series-connected coil (55) and a parallel-connected capacitor (56).

6. (currently amended) A circuit arrangement as claimed in ~~one of the preceding claims 2-5~~claim 2, characterized in that the parallel-connected capacitor (22, 23, 56) is formed at least partly by a parasitic capacitance between the lamp (24) and a metallic part.

7. (currently amended) A liquid crystal display on which a video signal of a computer or of a television set can be represented, comprising a circuit arrangement (1, 41, 51, 61) as claimed in ~~one of the preceding claims 1-6~~claim 1.